

1 to 10. (Cancelled)

12. (Canceled)

13. (Canceled)

{W:\03191\000M965000\00554021.DOC { }

15. (Currently Amended) A method of controlling an automated clutch of a vehicle, comprising the step of adapting a characteristic curve of the clutch through an electronic clutch management system, wherein the adaptation is performed under at least one suitable set of operating conditions, said suitable set of operating conditions being represented by at least one suitable operating point, wherein an adaptation algorithm is used for the adaptation of said characteristic curve, and wherein the adaptation algorithm performs adaptations of signals and parameters depending on the current operating point of the vehicle, wherein the adaptation algorithm employs at least one correction term The method of claim 13, wherein the at least one correction term comprises an engine torque correction value ( $\Delta M_{\text{engine}}$ ), which serves to take signal errors of the engine torque ( $M_{\text{engine}}$ ) into account.

{W:\03191\000M965000\00554021.DOC {XX}}



22. (Currently Amended) The method of claim [[12]] 20, wherein the at least one operating point is taken into account in the design of the adaptation algorithm.

23. (Canceled)

24. (Currently Amended) The method of claim [[23]] 25, wherein the first adaptation comprises adapting at least the friction coefficient through the steps of:

evaluating a dynamic equilibrium of the clutch and thereby determining a deviation between the torques acting on the clutch, and

adjusting the friction coefficient in accordance with said deviation.

25. (Currently Amended) A method of controlling an automated clutch of a vehicle, comprising the step of adapting a characteristic curve of the clutch through an electronic clutch management system, wherein the adaptation is performed under at least one suitable set of operating conditions, said suitable set of operating conditions being represented by at least one suitable operating point, wherein in the adaptation of the characteristic curve, a second adaptation is superimposed on a first adaptation ~~The method of claim 23~~, wherein the second adaptation comprises evaluating at least the shape of the characteristic curve.

26. (Previously presented) The method of claim 25, wherein evaluating said curve shape comprises

establishing a correction curve for the currently effective friction coefficient, and  
applying the correction curve to correct the deviations the actual characteristic curve  
and a nominal characteristic curve.

28. (Canceled)

comparing the computed clutch torque to a stored characteristic curve; and wherein a torque equilibrium at the automated clutch is represented by the equation:

wherein  $J_{\text{engine}}$  stands for a moment of inertia of the engine,  $d\omega_{\text{engine}}/dt$  stands for a rotary acceleration of the engine,  $M_{\text{engine}}$  stands for the engine torque, and  $M_{\text{clutch}}$  stands for the clutch torque The method of claim 28, wherein a clutch torque to be used in controlling the clutch and a torque error are calculated through the equation:

wherein  $M_{\text{clutch,control}}$  stands for the clutch torque value used by the control unit and  $\Delta M$  represents the torque error.

30. (Original) The method of claim 29, wherein the stored characteristic curve is corrected by the torque error.

31. (Original) The method of claim 30, wherein correcting the characteristic curve comprises adjusting a set of values representing the characteristic curve, said set of values comprising at least one of a friction coefficient and a point of incipient frictional engagement of the clutch.

32. (Previously Presented) The method of claim 29, wherein the friction coefficient is lowered if the torque error is positive, and the friction coefficient is increased if the torque error is negative.



wherein  $\omega_{\text{engine,model}}$  = model engine rpm-rate.

37. (Original) The method of claim 36, wherein the adaptation comprises the steps of comparing the model engine rpm-rate and the actual engine rpm-rate, and altering the characteristic curve based on deviations detected in said comparison.

38. (Original) The method of claim 37, wherein altering the characteristic curve comprises altering at least one descriptive quantity of the characteristic curve, said characteristic quantities comprising at least one of the friction coefficient and the point of incipient frictional engagement.

39. (Original) The method of claim 38, wherein the step of altering the characteristic curve is performed incrementally in order to avoid an unstable feedback condition.

40. (Original) The method of claim 38, wherein the friction coefficient is adapted in a plurality of adaptation steps for predetermined constraint points of a friction characteristic.

41. (Original) The method of claim 40, wherein said predetermined constraint points are located in a range of high clutch torque values.

42. (Original) The method of claim 41, wherein the friction coefficient is further adapted by an additional step of transferring the adaptation that was made for the predetermined



constraint points in the range of high torque values to other constraint points within a time period that includes the time during and after a full load cycle.

43. (New) The method of claim 15, wherein the at least one correction term comprises a correction value ( $\Delta_{TUP}$ ) for the clutch actuator displacement.

44. (New) The method of claim 15, wherein the at least one correction term comprises a characteristic curve parameter (CC parameter) which serves to adapt the friction coefficient of the automated clutch.

45. (New) The method of claim 44, wherein the CC parameter comprises a vector quantity.

46. (New) The method of claim 15, wherein a parameter identification is used in the design of the adaptation algorithm.